



# X900S-OPUS Static Receiver Specifications

Price (MSRP) <sup>1</sup>	<b>\$ 2,618</b> kit
GNSS Engine	NovAtel OEM6 (OEM615)
	
Measurements	120 channels, 3 constellations: GPS: L1C/A, L1C, L1P, L2 P(Y), L2C GLONASS: L1, L2 BeiDou: B1 5-hz rate
Post-Processing Static Performance (RMS) <sup>2</sup>	Horz 5 mm + 1 ppm Vert 10 mm + 1 ppm
Mounting	Standard 5/8" 11-TPI bottom mount
Initialization	Cold Start < 50 seconds; Hot Start < 35 seconds
Physical	Size (L x W x H): 7.5 x 7.9 x 3.3 in (190 x 200 x 84 mm) Weight: 3 lbs. 1 oz. (1.4 kg) with battery Operating temperature: -40°F to 149°F (-40°C to +65 °C) Storage temperature: -40°F to 167°F (-40°C to +75°C) Humidity: 100% condensation Waterproof and dust proof: IP67 protected from temporary, immersion to depth of 1-meter, floats Shock: survives a 2-meter drop to concrete
Electrical	Power consumption: 2 watts (0.275 A @ 7.4V) Lithium-Ion battery capacity: 2.2 Ah, 7.4 V, accepts 2.6 Ah extended Battery Life <sup>3</sup> : Up to 7-hours typical, 1,000 charge cycles External power input accepts 9 to 18 VDC Communication: 10-pin Lemo: USB: GPS Device mounts as an external drive Serial: RS232 Communications and Configuration Port Optional: Heavy Duty External Power Cable \$146
Internal Storage	4-GB Flash. ~170-days (5.6 months) storage with 5-second epochs, 7-years with 30-second epochs <sup>4</sup>
Warranty	2-year warranty; accessories 1-year; batteries 90-days

	<p><b>What is in the heavy-duty waterproof case?</b></p> <p>X900S-OPUS Precision Static GPS+GLO+BDU Receiver 2-Batteries Combination USB + Serial + Power Download Cable Dual-Charger with Power Supply, wall cord External Alligator-Clip Power Cable (for charger or head power) Hold-A-Pole Printed User's Manual iGage X9 Download and Submission Tool CD</p>
---	---



X900S-OPUS Complete Kit

<sup>1</sup> Price includes 3-day Shipping to most USA address.

<sup>2</sup> Precision and performance values assume a minimum of 9-satellites in multipath clear, EMI free, obstruction free environment with reasonable atmospheric conditions and satellite geometry. Post-processed accuracy is dependent on baseline length and time-on-point, 24-hour observations may be required. Stable mounts and generally accepted survey practices are required for the highest order survey results.

<sup>3</sup> Battery life varies with temperature and battery age. An external power source is recommended for static occupations lasting longer than 6-hours. Elevated and extreme cold working or storage temperatures (> 85°F, <-20°F) hasten capacity loss.

<sup>4</sup> Assuming 14-tracked satellites.

Prices, specifications and descriptions are subject to change without notice. Please call us for the latest information and a custom quotation.

[ Rev 5: 27 April 2015 ]



**iGage Mapping Corporation**  
1545 S 1100 E STE 1  
Salt Lake City Utah 84105 USA  
**+1-801-412-0011** [www.igage.com](http://www.igage.com)